

1 K3-F14-10110

Intel Core I3-10110u



CPU	Intel Core I3 10110U 2.10 GHz - 4.10GHz
Cores/Threads	2 Cores / 4 Threads
Cache	4 MB Cache
TDP	15W
Architecture	Products formerly Broadwell
Memory	2*DDR4L slot,support 32G max
Storage	SSD (M.2 SATA)
	Optional HDD (supports expansion of a 2.5-inch hard drive)
Audio Card	HD Audio realtek ALC 662
Graphics	Intel® UHD Graphics for 10th Gen Intel® Processors
Network	10/100/1000Mbps adaptive RTL 8111E
Extendable	WIFI+BT Module (Mini PCIE), support 4G module with available sim slot
OS Support	Windows (Not include XP) & Linux

I/O Ports	4*USB3.0、2*USB2.0、1*DP、2*HDMI、2*RJ45、1*DC、1*MIC-IN、1*LINE-OUT、1*TYPE-C、1*CLS、
------------------	---

BIOS Function

Display Mode	4K/ 3 displays (support copy mode,extended mode)	
	Max Resolution(DP): 4096x2160@60Hz; Max Resolution(HDMI): 4096*2160@30Hz	
Boot Mode	PXE / Auto-power-on / Wake-on-LAN	
Intel Virtualization	Support VT-x, VT-d	
Intel Hyper-Threading	Support	
Working Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)
Working Voltage	DC 12V - 5A	
Static Electricity	Contact discharge 2K, Air discharge 6K	
Storage Environment	Temperature: -10~60 °C	Relative Humidity: 0~95% (No Condensation)

2 K3-F14-10110

Intel Core I3-10110u



I/O Port

01	POWER ON/OFF	02	USB3.0*4	03	RESET
04	Type-C	05	MIC	06	SPK
07	Indicator light	08	USB2.0*2	09	RJ45 Gigabit LAN
10	RJ45 Gigabit LAN	11	DP	12	HDMI
13	HDMI	14	DC12V Input	15	/
16	Ground hole	17	Lock slot		
Size	L 133.8mm*W 126.6mm*H 47mm			Weight	Net : 1.0kg Gross : 1.8kg

Specification

Features	Adopt a plastic top cover with aluminum alloy body design; this top cover uses brushed texture with high gloss mirror effect.		
Heat Dissipation	with FAN		
Bracket	Dedicated bracket; Support VESA bracket		
Packing Box	Kraft paper color box + Anti-fall corrugated outer box		
Packing List	Power Adapter * 1	Power Cable * 1	Bracket * 1
	User Manual * 1	QA Card * 1	Screws * 1