K730-F1 **RK3576**













Product Features


- Built on advanced 8nm process with 64-bit octa-core architecture for high performance and low power consumption
- Integrated ARM Mali-G52 MC3 GPU with built-in 2D graphics acceleration engine
- 6 TOPS NPU, Support the installation of computing power sticks, empowering various Al scenarios.
- Supports 8K video encoding and decoding, with HDMI IN for image input
- Equipped with multiple display interfaces, enabling multi-screen independent output
- Integrated 48MP ISP for advanced image processing
- Supports high-speed expansion interfaces including PCIe, Type-C, and Gigabit Ethernet
- Compatible with Android and Linux operating systems


■ Interface Layout





Product Dimension





Product Specifications

System RK 3576 NPU 6 TOPS AI performance Support the installation of computing power sticks (M.2 2280 NVME) 8 GB Storage & Expansion Memory 64 GB eMMC storage; M.2 2280 NVMe SSD slot ARM Mali-G52 MC3, supports OpenGL ES 1.1 / 2.0 / 3.2, Vulkan 1.1, OpenCL 2.0 Full Profile; Integrated 2D Graphics Engine (RGA)	
Support the installation of computing power sticks (M.2 2280 NVME) Memory 8 GB Storage 64 GB eMMC storage; M.2 2280 NVMe SSD slot ARM Mali-G52 MC3, supports OpenGL ES 1.1 / 2.0 / 3.2, Vulkan 1.1,	
Memory 8 GB Storage 64 GB eMMC storage;	
& Expansion M.2 2280 NVMe SSD slot ARM Mali-G52 MC3, supports OpenGL ES 1.1 / 2.0 / 3.2, Vulkan 1.1,	
GPU	
Video Hardware Codec JPEG encoder/decoder; 8K video encoding (H.265/H.264); 8K 10-bit decoding (H.265/H.264/VP9/AV1)	
Display Interfaces HDMI IN ×1, HDMI OUT ×1, DP ×1	
Network Ethernet 2 × RJ45 ports, 10/100/1000 Mbps	
Wireless Network Dual-band WiFi (2.4G + 5G), Bluetooth supported	
USB 2 × USB 3.0, 4 × USB 2.0	
1/O 1 × RS232, 1 × RS485, 1 × Wiegand port	
Audio 1 × 3.5mm headphone out, 1 × 3.5mm microphone in	
SIM 1 × SIM card slot, supports internal 4G / 5G module	
Others Watchdog Customizable support	
RTC Supported	
Power Power Input DC 12V / 2A	
Input Buttons/Indicators Red/Green LED	
Chassis Dimensions 178mm × 105mm × 38mm (7.01 in × 4.13 in × 1.50 in)	
Physical Package Dimensions 213mm × 210mm × 50mm (8.39 in × 8.27 in × 1.97 in)	
Parameters Net Weight 0.68 kg (1.50 lbs)	
Gross Weight 1.3 kg (2.87 lbs)	
Software Operating System Android14.0 , Ubuntu22.04 , Debian11	
Operating -10°C ~ 40°C Temperature	
Storage Comperature Storage 0°C ~ 40°C	
Operating/Storage 0~85% RH (non-condensing)	
Humidity	



Product Model	CPU	Memory	Flash	LAN	RS485	RS232	HDMI	WiFi	TF	SIM
K730	RK3576	8 GB	64 GB (customizable)	2	1	1	2	1	0	1

■ Packing List

Accessories	Description
Power Adapter	DC 12V / 2A
WiFi Antenna	SMA ×1
VESA Mount Kit	Bracket ×1, Screw Pack ×1, Foot Pads ×4
User Manual	Universal ×1
Certificate of Compliance	Universal ×1

■ Optional Accessories

Accessories	Description
4G Module Kit	Quectel EC25-EC series module with antenna
Computing power stick	Hailo-8 26T computing power stick